

Attorney Docket #: E6026-500  
App. Serial No.: 10/825,516  
Art Unit: 3641

**Amendments to the Claims:**

The claims in this listing replace all prior claims in the application.

1-6. (cancelled)

7. (previously presented) An autoloading pistol with firing pin blocking magazine disconnect mechanism comprising:  
a frame that holds a magazine;  
a housing carried by the frame and defining a chamber to hold a cartridge;  
a firing pin disposed in the housing and movable toward the chamber;  
a blocking member movable into and out of engagement with the firing pin; and  
an actuator pivotally mounted to the frame that disengages the blocking member from the firing pin when the magazine is inserted in the pistol and engages the blocking member with the firing pin when the magazine is removed from the pistol so that the firing pin is prevented from moving toward and contacting a cartridge in the chamber, wherein the actuator is an ejector that expels spent cartridges from the pistol.

8. (cancelled)

9. (currently amended) The pistol of claim 7, wherein the housing is a reciprocating slide movable in a forward and rearward direction, and the blocking member is disposed in the movable slide.

10. (previously presented) An autoloading pistol with firing pin blocking magazine disconnect mechanism comprising:  
a frame that holds a magazine;  
a housing carried by the frame and defining a chamber to hold a cartridge;  
a firing pin disposed in the housing and movable toward the chamber;  
a blocking member movable into and out of engagement with the firing pin; and  
an actuator that disengages the blocking member from the firing pin when the magazine is inserted in the pistol and engages the blocking member with the firing pin when the magazine

Attorney Docket #: E6026-500  
App. Serial No.: 10/825,516  
Art Unit: 3641

is removed from the pistol so that the firing pin is prevented from moving toward and contacting a cartridge in the chamber, wherein the blocking member further comprises a shaft with a laterally-protruding flange, the flange movable into and out of engagement with the firing pin.

11. (original) The pistol of claim 10, wherein the flange engages a protrusion extending vertically upwardly from the firing pin to block the firing pin from moving toward the chamber.

12. (cancelled)

13. (cancelled)

14. (cancelled)

15. (currently amended) The pistol of claim 10 ~~12~~, wherein the actuator is pivotally movably mounted to the frame.

16. (currently amended) The pistol of claim 10 ~~12~~, wherein the actuator further comprises a body and angularly protruding lever arm configured to contact the blocking member.

17. (previously presented) An autoloading pistol with firing pin blocking magazine disconnect mechanism comprising:

a frame defining an open cavity;

a reciprocating slide carried by the frame and defining a chamber to hold a cartridge;

a firing pin movable toward the chamber;

a blocking member engageable with the firing pin and movable between a first position in which the blocking member does not engage and block forward movement of the firing pin, and a second position in which the blocking member engages and blocks forward movement of the firing pin; and

a blocking member actuator that holds the blocking member in the first position when supported by a magazine inserted in the frame, wherein removing the magazine from the pistol displaces the blocking member actuator in a first direction to concomitantly move the blocking

Attorney Docket #: E6026-500  
App. Serial No.: 10/825,516  
Art Unit: 3641

member to the second position in which forward movement of the firing pin toward the chamber is blocked, wherein the blocking member actuator is an ejector that ejects spent cartridges from the pistol.

18. (currently amended) The pistol of claim 17 ~~42~~, wherein the actuator maintains contact with the blocking member when the blocking member is in the first and second positions.

19. (currently amended) The pistol of claim 17 ~~42~~, wherein the blocking member is movable in a vertical direction between the first and second positions.

20. (canceled)

21. (canceled).

22. (currently amended) An autoloading pistol with firing pin blocking magazine disconnect mechanism comprising:

- a frame defining an open cavity; a reciprocating slide defining a chamber to hold a cartridge;

- a firing pin disposed in the slide and movable in a forward direction towards the chamber;

- a blocking member engageable with the firing pin and movable between a first disengaged position in which the blocking member allows the firing pin to move toward the chamber, and a second engaged position in which the blocking member does not allow the firing pin to move toward the chamber;

- a biasing member urging the blocking member into the second position; and

- an actuator that contacts the blocking member and is movable in response to inserting and removing a magazine from the frame, wherein the actuator is an ejector that expels spent cartridges from the pistol after discharge;

- wherein inserting the magazine displaces the actuator in a first direction to simultaneously move the blocking member into the first position, and

- wherein removing the magazine allows the biasing member to urge the blocking member

**Attorney Docket #: E6026-500**  
**App. Serial No.: 10/825,516**  
**Art Unit: 3641**

into the second position and simultaneously displace the actuator in a second direction opposite the first direction.

23. (original) The pistol of claim 22, wherein the actuator is pivotally mounted and movable in the frame, and includes a lever arm to operably engage the blocking member.

24. (original) The pistol of claim 22, wherein the blocking member is vertically movable between the first and second positions.

25. (original) The pistol of claim 24, wherein the actuator is vertically movable between an up position with the magazine inserted in the pistol and a down position with the magazine removed from the pistol.

26. (cancelled).